

Motherboard Asrock GE Pro-M2

Generalidades

GE Pro-M2 support 400/533Mhz FSB Intel Pentium 4 Processors. Packed with the features such as AGP 4X/onboard video, 2 PCI 2.2 slots, 1 AMR slot, ATA133, USB 2.0, 5+1 channels audio, 10/100Mbs Ethernet Lan, MicroATX form factor, ASRock U-COP™ and Hybrid Booster™ Technology.



Especificaciones

Processor

- > Support Intel® Pentium 4/Celeron Socket 478 Processors 400/533Mhz FSB

Chipset

- > North Bridge: Sis650GX, South Bridge : 962L

Audio

- > 5+1 Channels AC97 audio codec

Expansion Slots

- > 1 x AGP4X, 2 x PCI slots, 1 x AMR slot

I/O Interface

- > PS/2 Keyboard and Mouse Connectors
- > One Parallel and Serial port (via com port bracket)
- > 4 USB 2.0 ports
- > LAN and Video connector
- > Audio ports (Mic-in, Audio-in and out, Game port)
- > Dual IDE, support Ultra DMA 66/100/133 mode
- > Support 360K~2.88Mb, 3 Mode FDD or LS 120
- > ATX Power, a CPU and System Fan connectors

Memory

- > 2 x 184 pins DDR2700 slots (up to 2GB)

Video

- > Integrated with Real256 3D Graphic controller support 64MB Max shared memory

Lan

- > Onboard 10/100Mbps Ethernet controller

System Bios

- > AMI 2MB Flash ROM

Form Factor

- > MicroATX (9.6 x 9.6 inches)

Special Features

- > Support WOL, WOR, KB power ON/OFF and interrupt wake up from keyboard/mouse
- > Built-in ASRock U-COP™ CPU Overheating Protection and Hybrid Booster™ Technology
- > Built-in Thermal, Power and Fan Speed Monitor

DRIVERS

Driver & BIOS Page: http://www.asrock.com/support/Download/dl_gepro-m2.htm

Manual Download: http://www.asrock.com/Drivers/Manual/GEPro-HTR30-M2_UM.pdf